


2ch VGA video and audio transmitter

Description: This product is 2 channel active VGA Video & Audio transmitter allowing remote transmission of high-resolution VGA video and high-fidelity audio over UTP cable. In addition, This product provides one channel VGA Video & Audio output for local use.



【Certification】



【Features】

1. 350MHz signal transmission bandwidth.
2. High video resolution up to 1920×1080 pixels.
3. Powered by either power adaptor or optional USB power.
4. Support VGA, SVGA, XGA, SXGA, WXGA, UXGA and multi-sync monitors.
5. Built-in surge & transient protection with grounding rod on front panel.
6. Super interference rejection.

【Specification】

Power properties	Adaptive Voltage Arrange	12V DC(power adaptor)
	Power Consumption	<3.5w
	Connectors	DC Jack, USB-B
	USB Protecting Current	1000mA
Video properties	Video Input Connector	1* 15pin HD15 male; Impedance: 75Ω
	Local Video Output connector	1* 15pin HD15 female; Impedance: 75Ω
	UTP Cable Connector	2* RJ-45; Impedance: 50Ω
	Signal Transmission Band	>350MHz(-3db)
	Linear Distortion	<3%
	Synchronous signal	0-5V, TTL PWL

	Synchronous signal band	1K-200KHz
	DDC2	Virtual DDC
Audio properties	Connectors	2* 3.5mm Audio Jacks
	Input Impedance	10kΩ
	Output Impedance	600Ω
	Transmission Band	10-20KHz
Physical Properties	Dimensions (LWH)	95*65*28mm
	Housing Material	Metal
	Color	blue
	N.W.	540g
Environmental	Operating Temperature	0~70
	Relative Humidity(non-condensing)	10~85%
	Storage Temperature	-10~80
Accessories	Power Adaptor	Power supply input: 100-240V AC Power supply output: 12V DC/ 1Amp Wire Length:2m
Casing	Gross Weight	300g
	Casing Volume(LWH)	95*65*28mm

【Application】

