

Full HD Optical transmitter and receiver Model: LM-HF01

User Guide

Product Overview

HDMI Optical transmitter and receiver adopts the uncompressed digital HD video and high-speed digital optical fiber transmission technology advanced, It can transfer signal source (computer signal source, HDMI signal source high digital DVD/DVR) to long distance terminal easily, with strong performance, ensure the signal completed and stable.

Main features

- 1. Full digital, Uncompressed HD optical fiber transmission
- 2. Support Full HD 1920*1080@60Hz
- 3. All the two-way audio
- 4. Automatic identification and configure display mode
- 5. Automatic equalization inside, stable and clear graphics.
- 6. ESD protection circuit inside, to ensure the ESD damage.
- 7. Easily to installation, plug and play, no need to set up

Standard Package


Transmitter 1pcs

Receiver 1pcs

Power Supply Unit 5V/1A 2pcs

User Guide 1pcs

Interface overview



Installation

- 1. Connect HDMI input signal to HDMI_IN port by cable
- 2. Connect HDMI output signal to HDMI_OUT port by cable
- 3. Connect Audio input signal to AUDIO IN port
- 4. Connect Audio output signal to AUDIO OUT port
- 5. Connect FC fiber to OPT IN and OPT OUT
- 6. Power on.

Performance and Specification

Temperature	-5°C to +75°C
Humidity	5 to 90 % RH (no condensation)
Pixel band width	165MHz
Video format	800x600P60/1024x768P60 1280x800P60/1280x1024P60 1360x768P60 /1366x768P60 1400x1050P60/1440x900P60 1600x900P60/1600x1200P60 1680x1050P60/1280x720P50 1280x720P60/1920x1080P24 1920x1080P25/1920x1080P30 1920x1080P50/1920x1080P60 1920x1080I60 /1920x1080I50 1920x1200P60
The signa of Audio input and output	3.5MM Audio
Audio format	44.1K,48K,96K,176K,192K
RS232 port	3 ports industrial terminal
RS232 Baud rate	Support 115200 and all below
RS 232 Data bits	8 bits
Fiber port	FC
Fiber wavelength	1550/1310nm
Fiber band width	3Gbps
The Maximum transmission distance	10KM/20KM/40KM/60KM
Input voltage	DC 5V, inside+ outside-
Power consumption	receiver 4W transmitter 4W
Device size	110mm*580mm*25mm(length*width*height)
Packing box size	175mm*74mm*74mm (length*width*height)
Weight	1KG

Connection

